



Druid 18LCD

Features

- 7.6 Joule output energy
- Ideal choice for long distance series electric fencing systems that require monitoring
- Robust and flexible design for home, commercial security, industrial and game security and control.
- Built-in alarm monitors tampering or faults on the high voltage and earth fence wires
- Connectable to armed response radio or GSM module
- Lightning and power surge protection
- Intelligent power saving to extend battery life
- Easy-to-use tag included for controlling the energizer
- Walk test mode for easy fence testing
- The LCD background colour changes to easily identify the fence condition
- Powered by 240V mains and includes built-in battery for back-up power

- Built-in gate alarm input to monitor if the gate is open or closed
- Optional keypad for controlling and programming the energizer. This allows the user to control the energizer remotely, with up to two keypads

Specifications

Enclosure size: L370 x W232 x D145

Weight excluding battery (7AH): 4.8kg

Weight including battery (7AH): 7.0kg

IP rating: IPx4

Operating temperatures: -10°C to 50°C

Operating humidity: < 80% non-condensing

Electrical supply voltage: 240V

Typical power consumption (normal operating conditions): 25VA

Standby time (fully charged battery): 24hrs

Energy output 500 Ohms load 7.6 Joule

Open circuit voltage 9 600V

Enquire Now Dheran

➡  **084 704 2661**

 **dheran@spacesat.co.za**